

---

# DIGITAL AUDIO CABLE 1X2X0.22 BLACK 100 MT

Digital Audio Cable with  
double shielding 110 Ohm  
AES / EBU - 2x0.22 mm<sup>2</sup>

For digital audio and DMX  
cabling applications

Reference: CZZDMX801



Insulation in soft black PVC. External cable Diam.  $\approx$  6.20 ( $\pm$  0.10) mm. Second insulation in soft PVC - Diam.  $\approx$  4.40 ( $\pm$  0.10) mm. p>

O.F.C. Red Copper 100% spiral copper spiral.

+ O.F.C. tinned copper drainage wire

Core insulation with DPI, colored one red and one blue.

The conductors are wrapped together with recycled textile filling material.

Diam.  $\approx$  1.50 mm ( $\pm$  0.10) mm.

In tinned copper O.F.C. 28x0.10 mm.

Nom. Section 2x0.22 mm<sup>2</sup>

## **Properties:**

Conductor resistance: 79.15 Ohm / Km

Core / Core capacity: 50 pF / m

Core / Screen Capacity: 95 pF / m

Impedance: 110 Ohm

Maximum rated voltage: 49 V

Operating temperature: -15 / + 70  $\pm$  C

**RoHS3 Compliant: Ver. B / 16.05.19**