



Visit product page



FOS IQ PAR IP65 LIME

L006721

IP65



Contemporary IP65 led par with Wireless DMX operation and amazing color mixing, 19 LEDs 12 watts RGB + LIME , 26 degrees beam angle, 0-100% linear dimmer, flicker-free, 3 pixels rings, strobe effect with 1-25T /s, 22/10 DMX channel, IP rated power and DMX connector IN/OUT, Dual mounting brackets for installation/floor stand, Built, noise-free aluminum cooling system, built-in programs, and macro effects. 4.7 kg

TECHNICAL DETAILS

Light source / Optics

Based on 19 x 12 Watt RGB Lime LEDs.
50,000 hours approximate lifespan.
26 degrees beam angle.
Flicker-free operation, suitable for TV applications.

Effects

Red, Green, Blue, & Lime color mixing.
Preset colors/chases and color temperature adjustment DMX channel.
3 controllable independent ring LED sections (center, middle & outer).
Linear dimming & strobe.

Control

DMX / Auto & Sound operation.
Integrated wireless receiver, compatible with the AirLink series.
DMX control with 22 or 10 channels.

Technical Specifications

Power Supply: AC90 / 260 Volt, 50/60 Hz.

Power Consumption: 200 Watt.

IP65, suitable for outdoor use as well.

IP rated 3pin XLR & Truepowercon connectors.

Net Weight: 4,65 Kg

Gross Weight: 5,65 Kg

Dimensions: 155 x 299 x 279 mm (D x W x H).

Packing Dimensions: 370 x 335 x 245 mm (D x W x H).

Wireless Indicator Index

Wireless connection with the AirLink transmitters can be done in a simple way. The different colors and states will help you understand the status of the connection:

White: The fixture has been not paired with any transmitter yet. It is ready for pairing.

Red (flashing): The connection with the transmitter is lost.

Green (fast flashing): Connecting/pairing with the transmitter.

Green (slow flashing): Connected, with no DMX signal.

Green (steady on): Connected, with DMX signal.

PHOTOS



PRODUCT VIDEO



ACCESSORIES



FOS AirLink 24

AirLink DMX transmitter/
fader desk for the Solo a



FC-TP-PDC-1.5

Professional
TruePowercon/ DMX cable
1.5 meter.



FOS CLAMP 100

Professional clamp for
fixtures lifting weight 100



FOS Case IQ Par IP65

Flight case with wheels for
8pcs IQ Par IP65.



FOS AirLink PRO

AirLink DMX transmitter
for the Solo and Luminus P



FOS AirLink Foldable

AirLink DMX transmitter
for the Solo / Luminus / N

