



Visit product page



## FOS IQ PAR IP65 HEX

L006722

IP65



Contemporary IP65 led par with Wireless DMX operation and amazing color mixing, 19 LEDs 12 watts RGBW + Amber + UV, 26 degrees beam angle, 0-100% linear dimmer, flicker-free, 3 pixels rings, strobe effect with 1-25T /s, 22/10 DMX channel, IP rated power and DMX connector IN/OUT, Dual mounting brackets for installation/floor stand, Built, noise-free aluminum cooling system, built-in programs, and macro effects. 4.7 kg

### TECHNICAL DETAILS

#### Light source / Optics

Based on 19 x 12 Watt RGBWAUV LEDs.

50,000 hours approximate lifespan.

26 degrees beam angle.

Flicker-free operation, suitable for TV applications.

#### Effects

Red, Green, Blue, White, Amber, Ultra Violet color mixing.

Preset colors/chases and color temperature adjustment DMX channel.

3 controllable independent ring LED sections (center, middle & outer).

Linear dimming & strobe.

#### Control

DMX / Auto & Sound operation.

Integrated wireless receiver, compatible with the AirLink series.

DMX control with 30 or 12 channels.

## Technical Specifications

Power Supply: AC90 / 260 Volt, 50/60 Hz.

Power Consumption: 266 Watt.

IP65, suitable for outdoor use as well.

IP rated 3pin XLR & Truepowercon connectors.

Net Weight: 4,65 Kg

Gross Weight: 5,65 Kg

Dimensions: 155 x 299 x 279 mm (D x W x H).

Packing Dimensions: 370 x 335 x 245 mm (D x W x H).

## Wireless Indicator Index

Wireless connection with the AirLink transmitters can be done in a simple way. The different colors and states will help you understand the status of the connection:

**White:** The fixture has been not paired with any transmitter yet. It is ready for pairing.

**Red (flashing):** The connection with the transmitter is lost.

**Green (fast flashing):** Connecting/pairing with the transmitter.

**Green (slow flashing):** Connected, with no DMX signal.

**Green (steady on):** Connected, with DMX signal.

## PHOTOS



## PRODUCT VIDEO



## ACCESSORIES



**FOS AirLink PRO**

AirLink DMX transmitter for the Solo and Luminus P



**FOS AirLink 24**

AirLink DMX transmitter/ fader desk for the Solo a



**FOS Case IQ Par IP65**

Flight case with wheels for 8pcs IQ Par IP65.



**FC-TP-PDC-1.5**

Professional TruePowercon/ DMX cable for the Solo / Luminus / N 1.5 meter.



**FOS AirLink Foldable**

AirLink DMX transmitter for the Solo / Luminus / N



**FOS CLAMP 100**

Professional clamp for fixtures lifting weight 100

