

EUROLITE LED IP PAR 7x10W RGBL spot

IP65 spotlight with RGBL LEDs, frost filters and IR remote control

Art. No.: 51914226

GTIN: 4026397718485



List price: 355.81 €

incl. 19% VAT.

Features:

- 7 powerful LEDs 10 W high-power 4in1 QCL RGBL (homogenous color mix)
- Suitable for outdoor use
- Two additional frost filters provide a soft, homogeneous light
- 36 integrated show programs
- Control via IR remote control; stand-alone; DMX; Master/slave function; Sound to light via Microphone
- 3 buttons on the remote control for saving your own color mixes
- With a beam angle of 10°
- The device is cooled by passive convection cooling
- Flicker-free
- With double bracket
- OLED display
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; dimmer curves with adjustable response; white balance
- Strobe effect
- Direct color selection for 15 preset colors
- With a KENSINGTON LOCK theft protection
- Silent operation
- Mains input and output for power linking up to 8 units
- Preprogrammed in Light Captain
- With pressure compensation membrane

Package contents

- 1 x device, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 2 x diffuser cover, 2 x screw, 1 x mounting bracket

Logistic

EAN / GTIN: 4026397718485

Weight: 4,64 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.33 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED:	7 x 10 W high-power 4in1 QCL RRGBL (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; Master/slave function; Sound to light via Microphone
Preprogrammed in:	Light Captain
Beam angle:	10°
Beam angle (1/2 peak):	10° Frost filter 15° Frost filter 19°
Beam angle (1/10 peak):	20°
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Theft protection:	KENSINGTON LOCK
Dimensions:	Length: 23,4 cm Width: 28 cm Height: 17 cm
Weight:	4,25 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting