

## EUROLITE LED TMH-H180 Hybrid Moving-Head Spot/Wash COB

LED Moving Head hybrid spot/wash with rotating gobos, color wheel, prism and QuickDMX port

Art. No.: 51786085

GTIN: 4026397722390



**List price: 1188.81 €**

incl. 19% VAT.

### Features:

- Bright spotlight and full-fledged washlight in one device
- 1 powerful LED 200 W COB (chip-on-board) cold white (CW)
- 9 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Positioning within 540° PAN and 220° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold rotating; Focus motor-driven; gobo wheel with rotating gobos
- Color wheel with 8 dichroic filters plus open half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open slot-in gobo system for easy gobo replacement
- Shake effect
- Integrated show programs
- The device is cooled by temperature-controlled fan
- Preprogrammed in Light Captain; LED PC-Control 512
- Flicker-free
- With a beam angle of 10°
- Multicolor LCD display
- Dimmer electronic
- Control via stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); Master/slave function
- Gobo effect; Strobe effect
- With Omega bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Stage; Rental

### Logistic

EAN / GTIN: 4026397722390

Weight: 13,40 kg

Length: 0.54 m

Width: 0.44 m

Height: 0.31 m

- Application possibility: Standing; suspended

#### Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 2 x omega bracket

### Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	280 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 3,15 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 200 W COB (chip-on-board) cold white (CW) 9 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	220° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	1 - 20 Hz
Equipment:	Prism 3-fold rotating; Focus motor-driven; gobo wheel with rotating gobos
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 24mm Image diameter 16mm Slot-in gobo system for easy gobo replacement Shake effect
DMX channels:	21; 23
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; Sound to light via Microphone; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); Master/slave function
Preprogrammed in:	Light Captain; LED PC-Control 512
Beam angle:	10°
Beam angle (1/2 peak):	Spot 10° Wash effect 14°
Beam angle (1/10 peak):	Wash effect 30°
Illuminance in Lux (lx):	Spot cold white (CW) 3m: 21934 lx, 6m: 5598 lx Wash effect red (R) 1m: 1430 lx, 3m: 160 lx, 6m: 41 lx

Wash effect green (G) 1m: 1495 lx, 3m: 171 lx,  
6m: 41 lx

Wash effect blue (B) 1m: 604 lx, 3m: 66 lx, 6m:  
17 lx

Wash effect cold white (CW) 1m: 4241 lx, 3m:  
481 lx, 6m: 123 lx

Wash effect all 1m: 7407 lx, 3m: 829 lx, 6m: 206  
lx

---

Housing color:	Black
Attachment system:	2x Omega bracket
Display type:	Multicolor LCD display
Dimensions:	Width: 32,0 cm Depth: 22,5 cm Height: 45,0 cm
Weight:	12,00 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

---