eurolite®

EUROLITE Set LED B-40 HCL MK2 white + Soft Bag

Art. No.: 20000994 GTIN: 4026397728514





incl. 19% VAT.

Features:

EUROLITE LED B-40 HCL Beam Effect MK2 wh

LED beam effect with RGBWA+UV color mixing, incl. remote-control

- 8 integrated show programs
- Control via IR remote control; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Master/slave function
- Multi beam effect; Strobe effect
- Monochrome 4 digit 7-segment LED display
- 5 powerful LEDs 10 W 6in1 HCL RGBWA/UV
 segments controlled separately
- Color blend stepless; Dimmer electronic; Rotation speed stepless
- With Omega bracket
- Preprogrammed in Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
- For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended Package contents
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x omega bracket, 4 x screw, 4 x washer, 1 x remote control, 1 x battery

EUROLITE SB-10 Soft Bag

Black soft bag with divider, 330 x 330 x 355 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With divider
- With Outside pocket

Logistic

EAN / GTIN: 4026397728514 Weight: 7,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 Rugged carrying handles

Technical specifications:

Weight:	6,50 kg

EUROLITE LED B-40 HCL Beam Effect MK2 wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	56 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1,6 A Fuse replaceable
Lamp type:	LED lamp
LED:	5 x 10 W 6in1 HCL RGBWA/UV
Flash rate:	0 - 20 Hz
DMX channels:	3; 12; 23
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	IR remote control; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Master/slave function
Preprogrammed in:	Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
Housing color:	White
Attachment system:	Omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Length: 32,00 cm Width: 32,00 cm Height: 39,00 cm
Weight:	4,22 kg
Noise classification:	Class 2 (slight noise)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
0 1	
Special product:	Not designed for household room illumination

EUROLITE SB-10 Soft Bag

Maximum load:	25 kg	
Carrying handle:	2 pc/pcs	
Material:	Nylon	
Color:	Black, water repellent	
Dimensions:	Width: 33 cm	
	Depth: 37 cm	
	Height: 33 cm	
Weight:	440 g	