

## EUROLITE LED PIX-144 RGBW Bar

LED light bar with 144 wide beam SMD LEDs in RGBW and pixel control

Art. No.: 51930351

GTIN: 4026397708561



**List price: 153.51 €**

incl. 19% VAT.

### Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 144 powerful LEDs SMD 5050 4in1 QCL RGBW (homogenous color mix)<BR>8 segments controlled separately
- Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Strobe effect
- 16 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; Master/slave function; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 120°
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; Wall mounting

#### Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x diffusor cover

### Logistic

EAN / GTIN: 4026397708561

Weight: 1,94 kg

Length: 1.03 m

Width: 0.12 m

Height: 0.11 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	144 x SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	6; 9; 16; 30; 58
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; Master/slave function; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	2x Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Metal
Dimensions:	Length: 1,085 m Depth: 6,5 cm Height: 9,0 cm
Weight:	1,63 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting