

EUROLITE Set 4x AKKU IP Flat Light 1 chrome + Soft Bag

Set with 4 wireless battery-powered LED spotlights, chrome edition with soft bag

Art. No.: 20000425

GTIN:



List price: 1188.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP Flat Light 1 cr

Flat chrome spotlight with 15 W RGBW LED, QuickDMX transceiver and bracket

- Integrated QuickDMX transceiver for wireless DMX control
- Chrome housing
- Battery operation up to 18h depending on program used
- 1 powerful LED 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; IR remote control; DMX
- Flicker-free
- With a beam angle of 8°
- With Mounting bracket
- OLED display
- Suitable for outdoor use IP65
- For application areas such as: Small rental; Wedding/gala/events; mobile djs / entertainer; video and photography
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Application possibility: Standing

Package contents

Logistic

- 1 x device, 1 x external mains adapter, 1 x remote control, 1 x battery, 1 x declaration of conformity, 1 x user manual

EUROLITE SB-14 Soft-Bag

Practical black soft bag, divided into 4 compartments, for 4 AKKU Flat Lights

- With 2 Outside pockets
- With 4 compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 Rugged carrying handles

Technical specifications:

Weight: 6,85 kg

EUROLITE AKKU IP Flat Light 1 cr

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 2,5 A
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Battery pack type:	2 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED:	1 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; QuickDMX; IR remote control; DMX
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	8°
Beam angle (1/2 peak):	8°
Housing color:	Silver
Attachment system:	Mounting bracket
Display type:	OLED display
Carrier frequency:	2,4 GHz
Dimensions:	Width: 17,2 cm Depth: 13,8 cm Height: 6,4 cm

Weight:	1,63 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-14 Soft-Bag

Carrying handle:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Dimensions:	Width: 28 cm Depth: 22 cm Height: 18 cm
Weight:	340 g