eurolite®

EUROLITE LED CAT-80 Beam Effect wh

LED Beam Effect with 80 W COB LED in cold white and gobo wheel

Art. No.: 51918596 GTIN: 4026397719635











List price: 474.81 €

incl. 19% VAT.

Features:

- 3 different motion axes

- Rotating faceted mirror inside
- Rotating and swiveling mirror cylinder
- Generates countless moving patterns in the room
- 1 powerful LED 80 W COB (chip-on-board) cold white (CW)
- Gobo wheel with static gobos; Focus manual
- Dimmer electronic
- Mirror cylinder effect; Strobe effect
- Gobo wheel with static gobos, 9 color gobos and open
- The device is cooled by cooling fan
- Control via stand-alone; Master/slave function; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light'J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- OLED display
- For application areas such as: Clubs/dancing school; Party room; Stage; mobile djs / entertainer; Rental
- Application possibility: Suspended; on stand Package contents
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x xLR cable

Logistic

EAN / GTIN: 4026397719635 Weight: 4,08 kg Length: 0.40 m Width: 0.35 m Heigth: 0.24 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 80 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 25 Hz
Equipment:	Gobo wheel with static gobos; Focus manual
Gobos:	Gobo wheel with static gobos, 9 color gobos and open
DMX channels:	7
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; Master/slave function; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
Housing color:	White
Display type:	OLED display
Dimensions:	Width: 29,0 cm Depth: 18,5 cm
	Height: 31,5 cm
Weight:	3,12 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting