

EUROLITE LED THA-500F Theater Spot

Fresnel spot, 450 W COB LED in warm white, DMX

Art. No.: 41602180

GTIN: 4026397731569



List price: 1486.31 €

incl. 19% VAT.

Features:

- Rugged metal housing
- Rubber-coated handle
- 1 powerful LED 450 W COB (chip-on-board) warm white (WW)
- Zoom motor-driven; Zoom manual
- Dimmer curves with adjustable response; Dimmer electronic; pulse-width modulation variable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; Rotary dial for brightness; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- With a beam angle of 8° - 56°
- Very high color rendering index (CRI)
- With Mounting bracket
- Monochrome LCD display
- 4 rubber feet
- Mains input and output for power linking up to 4 units
- Application possibility: Standing; suspended
- Built with SEETRONIC connector
- For application areas such as: Trade fair and shop fitting; Stage; theater; Rental
- Very quiet working noise

Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual, 1 x barndoor

Logistic

EAN / GTIN: 4026397731569

Weight: 13,30 kg

Length: 0.59 m

Width: 0.41 m

Height: 0.41 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	475 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 6,3 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 450 W COB (chip-on-board) warm white (WW)
Equipment:	Zoom motor-driven; Zoom manual
DMX channels:	1; 2; 4; 8
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; Rotary dial for brightness; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
Projection:	Flicker-free
Beam angle:	8° - 56°
Beam angle (1/2 peak):	8 - 43°
Beam angle (1/10 peak):	15 - 56°
Color temperature:	3000K
Color rendering index (CRI):	96 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome LCD display
Transport aid:	4 x rubber feet
Use of brands:	Built with SEETRONIC connector
Dimensions:	Length: 44,0 cm Width: 34,0 cm Height: 43,5 cm
Weight:	10,45 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting