

# MA20DW/8

MA20DW/8



## MOUNTING INFORMATION

|                        |             |
|------------------------|-------------|
| Overall Diameter       | 210 mm (8") |
| Bolt Circle Diameter   | 196 mm      |
| Baffle cutout Diameter | 181 mm      |
| Depth                  | 85 mm       |
| Mounting Depth         | 78 mm       |
| Net Weight             | 1,3 Kg      |

## SPECIFICATIONS

|                     |            |
|---------------------|------------|
| Nominal Impedance   | 8 Ohm      |
| RMS Power           | 150 W      |
| MAX Power           | 300 W      |
| Sensitivity (1W/1m) | 92 dB      |
| Frequency Range     | 55-5000 Hz |
| Voice Coil Diameter | 30 mm      |
| Magnet              | Ferrite    |
| Magnet weight       | 20 Oz      |
| Basket Material     | Steel      |

## THIELE AND SMALL PARAMETERS

|            |                        |
|------------|------------------------|
| Re         | 4.000 Ohm              |
| Qes        | 0.975                  |
| Qms        | 2.488                  |
| Qts        | 0.701                  |
| Vas        | 28.551 l               |
| Sd         | 213.83 cm <sup>2</sup> |
| Mms        | 21.269 gr              |
| Bl         | Bl 6.012 TM            |
| Mmd        | 19.472 mkg             |
| Cms        | 439.783 uM/N           |
| Efficiency | 0.40 %                 |